

This Manufacturer Certification Statement is provided to certify that the exterior door slabs listed below, when installed properly, meet the specific energy efficiency criteria in Internal Revenue Code, Section 25C, as it is applied in the American Recovery and Reinvestment Act (ARRA). This document should be retained by the taxpayer as it may be requested from the Internal Revenue Service (IRS) in the event of an audit. It is also recommended that taxpayers retain all product labeling associated with energy usage. Homeowners should consult with their tax advisor to confirm that they qualify for the tax credit, as this document is intended solely to list those products that meet the criteria, and not as an assurance that a homeowner will qualify for the tax credit. For specific information on how to qualify for the tax credit, please visit the IRS website.

Taylor Building Products stipulates compliance with NFRC requirements to the standards listed below, using the most current NFRC approved spectral data.

85222.01-201-45 ATI Expires 8/28/2012

5/4/2009

Thermal Performance Test

NFRC 100 - Procedure for Determining Fenestration Product U-Factors

NFRC 200 - Procedure for Determining Fenestration Product SHGC and VT

NFRC 500 - Procedure for Determining Fenestration Product Condensation Resistance Values

TAYLOR STEEL EDGE DOOR

Glass/Door Type	1/2" Glass, Clear, Air		1/2" Glass, Clear, Air		1/2" Glass, Low E, Air		1/2" Glass, Low E, Air		1/2" Glass, Low E, Argon		1/2" Glass, Low E, Argon	
	U-Factor	SHGC	U-Factor	SHGC	U-Factor	SHGC	U-Factor	SHGC	U-Factor	SHGC	U-Factor	SHGC
Embossed Panel (0.18)	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
1/4 Lite	0.2	0.03	0.2	0.02	0.2	0.02	0.2	0.02	0.2	0.02	0.2	0.02
1/2 Lite	0.32	0.2	0.29	0.11	0.29	0.11	0.27	0.11	0.27	0.11	0.27	0.11
3/4 Lite	0.38	0.29	0.33	0.16	0.33	0.16	0.31	0.16	0.31	0.16	0.31	0.16
Full Lite	0.4	0.32	0.35	0.18	0.35	0.18	0.32	0.17	0.32	0.17	0.32	0.17

Glass/Door Type	1" Glass, Clear, Air		1" Glass, Clear, Air		1" Glass, Low E, Air		1" Glass, Low E, Air		1" Glass, Low E, Argon		1" Glass, Low E, Argon	
	U-Factor	SHGC	U-Factor	SHGC	U-Factor	SHGC	U-Factor	SHGC	U-Factor	SHGC	U-Factor	SHGC
Embossed Panel (0.18)	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
1/4 Lite	0.2	0.03	0.2	0.02	0.2	0.02	0.2	0.02	0.2	0.02	0.2	0.02
1/2 Lite	0.31	0.2	0.26	0.11	0.26	0.11	0.25	0.11	0.25	0.11	0.25	0.11
3/4 Lite	0.36	0.29	0.3	0.16	0.3	0.16	0.28	0.16	0.28	0.16	0.28	0.16
Full Lite	0.38	0.32	0.32	0.17	0.32	0.17	0.30	0.17	0.30	0.17	0.30	0.17

Glass/Door Type	1" Glass, Clear, Argon		1" Glass, Clear, Argon	
	U-Factor	SHGC	U-Factor	SHGC
Embossed Panel (0.18)	n/a	n/a	n/a	n/a
1/4 Lite	0.2	0.03	0.2	0.03
1/2 Lite	0.30	0.2	0.30	0.2
3/4 Lite	0.35	0.29	0.35	0.29
Full Lite	0.37	0.32	0.37	0.32

Glass/Door Type	1" Decorative, Air		1" Decorative, Air		1" Decorative, Low E, Argon		1" Decorative, Low E, Argon	
	U-Factor	SHGC	U-Factor	SHGC	U-Factor	SHGC	U-Factor	SHGC
Embossed Panel (0.18)	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
1/4 Lite	0.2	0.05	0.2	0.03	0.2	0.03	0.19	0.03
1/2 Lite	0.27	0.16	0.25	0.09	0.25	0.09	0.24	0.09
3/4 Lite	0.31	0.24	0.28	0.13	0.28	0.13	0.26	0.13
Full Lite	0.32	0.26	0.29	0.15	0.29	0.15	0.27	0.15

Glass/Door Type	1" Decorative, Argon		1" Decorative, Argon	
	U-Factor	SHGC	U-Factor	SHGC
Embossed Panel (0.18)	n/a	n/a	n/a	n/a
1/4 Lite	0.20	0.05	0.20	0.05
1/2 Lite	0.26	0.16	0.26	0.16
3/4 Lite	0.30	0.24	0.30	0.24
Full Lite	0.31	0.26	0.31	0.26

NOTES: All Low-E glass is Guradian PPII LowE (e = 0.044), SHGC for clear glass units is without grids.

1/4, 1/2, 3/4 lites values are from embossed panel data, Full lite data is from flush panels

Full testing information available upon request

Meets or exceeds combined requirements for a maximum U-factor of 0.30 and SHGC of 0.30

Under penalties of perjury, I declare that I have examined this certification statement, and to the best of my knowledge and belief, the facts are true, correct, and complete.

K R B

Kevin R. Bulow
Product and R&D Manager
5/4/2009

This Manufacturer Certification Statement is provided to certify that the exterior door slabs listed below, when installed properly, meet the specific energy efficiency criteria in Internal Revenue Code, Section 25C, as it is applied in the American Recovery and Reinvestment Act (ARRA). This document should be retained by the taxpayer as it may be requested from the Internal Revenue Service (IRS) in the event of an audit. It is also recommended that taxpayers retain all product labeling associated with energy usage. Homeowners should consult with their tax advisor to confirm that they qualify for the tax credit, as this document is intended solely to list those products that meet the criteria, and not as an assurance that a homeowner will qualify for the tax credit. For specific information on how to qualify for the tax credit, please visit the IRS website.

Taylor Building Products stipulates compliance with NFRC requirements to the standards listed below, using the most current NFRC approved spectral data.

85221.01-201-45 ATI Expires 8/26/2012

5/4/2009

Thermal Performance Test

NFRC 100 - Procedure for Determining Fenestration Product U-Factors

NFRC 200 - Procedure for Determining Fenestration Product SHGC and VT

NFRC 500 - Procedure for Determining Fenestration Product Condensation Resistance Values

TAYLOR WOOD EDGE STEEL DOOR - EDGEWOOD

Glass/Door Type	1/2" Glass, Clear, Air		1/2" Glass, Clear, Air		1/2" Glass, Low E, Air		1/2" Glass, Low E, Air		1/2" Glass, Low E, Argon		1/2" Glass, Low E, Argon	
	U-Factor	SHGC	U-Factor	SHGC	U-Factor	SHGC	U-Factor	SHGC	U-Factor	SHGC	U-Factor	SHGC
Embossed Panel (0.12)	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
1/4 Lite	0.15	0.03	0.15	0.02	0.14	0.02	0.14	0.02	0.21	0.11	0.21	0.11
1/2 Lite	0.26	0.2	0.23	0.11	0.23	0.11	0.21	0.11	0.25	0.16	0.25	0.16
3/4 Lite	0.33	0.29	0.28	0.16	0.28	0.16	0.25	0.16	0.27	0.17	0.27	0.17
Full Lite	0.35	0.32	0.29	0.17	0.29	0.17	0.27	0.17	0.27	0.17	0.27	0.17

Glass/Door Type	1" Glass, Clear, Air		1" Glass, Clear, Air		1" Glass, Low E, Air		1" Glass, Low E, Air		1" Glass, Low E, Argon		1" Glass, Low E, Argon	
	U-Factor	SHGC	U-Factor	SHGC	U-Factor	SHGC	U-Factor	SHGC	U-Factor	SHGC	U-Factor	SHGC
Embossed Panel (0.12)	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
1/4 Lite	0.15	0.03	0.14	0.02	0.14	0.02	0.14	0.02	0.20	0.11	0.20	0.11
1/2 Lite	0.25	0.2	0.21	0.11	0.21	0.11	0.20	0.11	0.23	0.15	0.23	0.15
3/4 Lite	0.31	0.29	0.25	0.16	0.25	0.16	0.23	0.15	0.24	0.17	0.24	0.17
Full Lite	0.33	0.32	0.26	0.17	0.26	0.17	0.24	0.17	0.24	0.17	0.24	0.17

Glass/Door Type	1" Glass, Clear, Argon		1" Glass, Clear, Argon	
	U-Factor	SHGC	U-Factor	SHGC
Embossed Panel (0.12)	n/a	n/a	n/a	n/a
1/4 Lite	0.15	0.03	0.15	0.03
1/2 Lite	0.25	0.2	0.25	0.2
3/4 Lite	0.30	0.29	0.30	0.29
Full Lite	0.32	0.32	0.32	0.32

Glass/Door Type	1" Decorative, Air		1" Decorative, Air		1" Decorative, Low E, Argon		1" Decorative, Low E, Argon	
	U-Factor	SHGC	U-Factor	SHGC	U-Factor	SHGC	U-Factor	SHGC
Embossed Panel (0.12)	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
1/4 Lite	0.14	0.05	0.14	0.03	0.14	0.03	0.14	0.03
1/2 Lite	0.21	0.16	0.19	0.09	0.19	0.09	0.18	0.09
3/4 Lite	0.25	0.24	0.22	0.13	0.22	0.13	0.21	0.13
Full Lite	0.27	0.26	0.24	0.15	0.24	0.15	0.22	0.14

Glass/Door Type	1" Decorative, Argon		1" Decorative, Argon	
	U-Factor	SHGC	U-Factor	SHGC
Embossed Panel (0.12)	n/a	n/a	n/a	n/a
1/4 Lite	0.14	0.05	0.14	0.05
1/2 Lite	0.21	0.16	0.21	0.16
3/4 Lite	0.24	0.24	0.24	0.24
Full Lite	0.25	0.26	0.25	0.26

NOTES: All Low-E glass is Guradian PPII LowE (e = 0.044), SHGC for clear glass units is without grids.

1/4, 1/2, 3/4 lites values are from embossed panel data, Full lite data is from flush panels

Full testing information available upon request

Meets or exceeds combined requirements for a maximum U-factor of 0.30 and SHGC of 0.30

Under penalties of perjury, I declare that I have examined this certification statement, and to the best of my knowledge and belief, the facts are true, correct, and complete.

K R B

Kevin R. Bulow
Product and R&D Manager
5/4/2009

This Manufacturer Certification Statement is provided to certify that the exterior door slabs listed below, when installed properly, meet the specific energy efficiency criteria in Internal Revenue Code, Section 25C, as it is applied in the American Recovery and Reinvestment Act (ARRA). This document should be retained by the taxpayer as it may be requested from the Internal Revenue Service (IRS) in the event of an audit. It is also recommended that taxpayers retain all product labeling associated with energy usage. Homeowners should consult with their tax advisor to confirm that they qualify for the tax credit, as this document is intended solely to list those products that meet the criteria, and not as an assurance that a homeowner will qualify for the tax credit. For specific information on how to qualify for the tax credit, please visit the IRS website.

Taylor Building Products stipulates compliance with NFRC requirements to the standards listed below, using the most current NFRC approved spectral data.

85223.01-201-45 ATI Expires 9/2/2012

5/4/2009

Thermal Performance Test

NFRC 100 - Procedure for Determining Fenestration Product U-Factors

NFRC 200 - Procedure for Determining Fenestration Product SHGC and VT

NFRC 500 - Procedure for Determining Fenestration Product Condensation Resistance Values

TAYLOR STEEL URETHANE SIDELIGHT

Glass/Sidelight Type	1/2" Glass, Clear, Air		1/2" Glass, Clear, Air		1/2" Glass, Low E, Air		1/2" Glass, Low E, Air		1/2" Glass, Low E, Argon		1/2" Glass, Low E, Argon	
	U-Factor	SHGC	U-Factor	SHGC	U-Factor	SHGC	U-Factor	SHGC	U-Factor	SHGC	U-Factor	SHGC
Embossed Panel (0.14)	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
1/4 Lite	0.18	0.03	0.17	0.02	0.17	0.02	0.17	0.02	0.25	0.12	0.25	0.12
1/2 Lite	0.31	0.21	0.27	0.12	0.27	0.12	0.27	0.12	0.3	0.17	0.3	0.17
3/4 Lite	0.38	0.32	0.33	0.17	0.33	0.17	0.33	0.17	0.3	0.17	0.3	0.17
Full Lite	0.29	0.37	0.27	0.20	0.27	0.20	0.27	0.20	0.25	0.2	0.25	0.2

Glass/Sidelight Type	1" Glass, Clear, Air		1" Glass, Clear, Air		1" Glass, Low E, Air		1" Glass, Low E, Air		1" Glass, Low E, Argon		1" Glass, Low E, Argon	
	U-Factor	SHGC	U-Factor	SHGC	U-Factor	SHGC	U-Factor	SHGC	U-Factor	SHGC	U-Factor	SHGC
Embossed Panel (0.14)	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
1/4 Lite	0.18	0.03	0.17	0.02	0.17	0.02	0.17	0.02	0.24	0.12	0.24	0.12
1/2 Lite	0.3	0.22	0.25	0.12	0.25	0.12	0.25	0.12	0.28	0.17	0.28	0.17
3/4 Lite	0.36	0.32	0.3	0.17	0.3	0.17	0.3	0.17	0.28	0.17	0.28	0.17
Full Lite	0.29	0.37	0.26	0.2	0.26	0.2	0.26	0.2	0.25	0.2	0.25	0.2

Glass/Sidelight Type	1" Glass, Clear, Argon		1" Glass, Clear, Argon	
	U-Factor	SHGC	U-Factor	SHGC
Embossed Panel (0.14)	n/a	n/a	n/a	n/a
1/4 Lite	0.18	0.03	0.18	0.03
1/2 Lite	0.28	0.22	0.28	0.22
3/4 Lite	0.36	0.32	0.36	0.32
Full Lite	0.28	0.37	0.28	0.37

Glass/Sidelight Type	1" Decorative, Air		1" Decorative, Air		1" Decorative, Low E, Argon		1" Decorative, Low E, Argon	
	U-Factor	SHGC	U-Factor	SHGC	U-Factor	SHGC	U-Factor	SHGC
Embossed Panel (0.14)	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
1/4 Lite	0.17	0.04	0.17	0.02	0.16	0.02	0.16	0.02
1/2 Lite	0.25	0.2	0.23	0.11	0.22	0.11	0.22	0.11
3/4 Lite	0.30	0.30	0.27	0.16	0.25	0.16	0.25	0.16
Full Lite	0.25	0.31	0.24	0.18	0.23	0.17	0.23	0.17

Glass/Sidelight Type	1" Decorative, Argon		1" Decorative, Argon	
	U-Factor	SHGC	U-Factor	SHGC
Embossed Panel (0.14)	n/a	n/a	n/a	n/a
1/4 Lite	0.17	0.04	0.17	0.04
1/2 Lite	0.25	0.2	0.25	0.2
3/4 Lite	0.29	0.30	0.29	0.30
Full Lite	0.24	0.31	0.24	0.31

NOTES: All Low-E glass is Guradian PPII LowE (e = 0.044), SHGC for clear glass units is without grids. 1/4, 1/2, 3/4 lites values are from embossed panel data, Full lite data is from flush panels. Full testing information available upon request.

Meets or exceeds combined requirements for a maximum U-factor of 0.30 and SHGC of 0.30

Under penalties of perjury, I declare that I have examined this certification statement, and to the best of my knowledge and belief, the facts are true, correct, and complete.

K R B

Kevin R. Bulow
Product and R&D Manager
5/4/2009