



# FLORIDA & WIND BORNE REGIONS PRODUCT APPROVALS

## MULTI-POINT FIBERGLASS

### SHUTTERED APPLICATIONS\*

ODL Non-Impact Doorglass, Wood or Composite Frames

### 6/8-8/0 GLAZED DOORS

Florida #	Config. X=Door O=Sidelight	Unit Size (up to)	Impact Rated	Swing	Design Pressure Rating
13158.1	X, OX or XO, OXO	9/0 x 7/0	No	Inswing / Outswing	+45/-45
13158.2	XX, OXXO	12/0 x 7/0	No	Inswing / Outswing	+45/-45
13158.9	X, OX or XO, OXO	9/0 x 8/0	No	Inswing / Outswing	+45/-45
13158.10	XX, OXXO	12/0 x 8/0	No	Inswing / Outswing	+45/-45

### 6/8-8/0 SOLID/OPAQUE DOORS

Florida #	Config. X=Door O=Sidelight	Unit Size (up to)	Impact Rated	Swing	Design Pressure Rating
13158.3	X, OX or XO, OXO	9/0 x 7/0	No	Inswing / Outswing	(IS) X:+55/-60 XO/OXO:+45/-45 (OS) X:+55/-55 XO/OXO:+45/-45
13158.4	XX, OXXO	12/0 x 7/0	No	Inswing / Outswing	(IS) XX:+50/-55 OXXO:+45/-45 (OS) XX:+50/-50 OXXO:+45/-45
13158.11	X, OX or XO, OXO	9/0 x 8/0	No	Inswing / Outswing	(IS) X:+55/-60 XO/OXO:+45/-45 (OS) X:+55/-55 XO/OXO:+45/-45
13158.12	XX, OXXO	12/0 x 8/0	No	Inswing / Outswing	(IS) XX:+50/-55 OXXO:+45/-45 (OS) XX:+50/-50 OXXO:+45/-45

### UNSHUTTERED APPLICATIONS w/ GLAZED SIDELIGHTS

ODL Impact Doorglass, Wood or Composite Frames

### 6/8-8/0 GLAZED DOORS

Florida #	Config. X=Door O=Sidelight	Unit Size (up to)	Impact Rated	Swing	Design Pressure Rating
13158.5	X, OX or XO, OXO	9/0 x 7/0	Yes	Inswing / Outswing	(IS) +50/-55 (OS) +50/-50
13158.6	XX, OXXO	12/0 x 7/0	Yes	Inswing / Outswing	(IS) +50/-55 (OS) +50/-50
13158.13	X, OX or XO, OXO	9/0 x 8/0	Yes	Inswing / Outswing	(IS) +50/-55 (OS) +50/-50
13158.14	XX, OXXO	12/0 x 8/0	Yes	Inswing / Outswing	(IS) +50/-55 (OS) +50/-50

### 6/8-8/0 SOLID/OPAQUE DOORS

Florida #	Config. X=Door O=Sidelight	Unit Size (up to)	Impact Rated	Swing	Design Pressure Rating
13158.7	X, OX or XO, OXO	9/0 x 7/0	Yes	Inswing / Outswing	(IS) +50/-55 (OS) +50/-50
13158.8	XX, OXXO	12/0 x 7/0	Yes	Inswing / Outswing	(IS) +50/-55 (OS) +50/-50
13158.15	X, OX or XO, OXO	9/0 x 8/0	Yes	Inswing / Outswing	(IS) X:+55/-60 XO/OXO:+45/-45 (OS) X:+55/-55 XO/OXO:+45/-45
13158.16	XX, OXXO	12/0 x 8/0	Yes	Inswing / Outswing	(IS) +50/-55 (OS) +50/-50